



BALUN CAB

Balún pasivo con cable



- Color video hasta 400m. con balún pasivo via UTP cat5e/6
- Dos terminales con tornillo
- Excelente rechazo a interferencias
- Protección contra sobretensiones incorporada (TVS)
- Conector BNC macho con tramo de cable de 165mm

Modelo	BALUN CAB
Product Name	Single Channel Passive Video Transceiver
Applied Devices	CCTV cameras, monitors, DVR, switchers, IP encoders, and other CCTV equipment
Video	Video Format PAL, NTSC, SECAM Operating Frequency DC to 5MHz Max Distance UTP Category 5e (24AWG) Color: 1300ft(400m) B & W: 1950ft(600m) Common-mode/Differential-mode rejection 15 KHz to 5 MHz 60 dB typ Impedance Coax, Male BNC 75 ohms UTP, Screw terminal 100 ohms
Wire Type	Video Distance Adjustment 0.5 dB typ Network Wiring One Unshielded Twisted Pair (for each video signal) 24-16 AWG (0.5-1.31mm) Category Type 2 or better Impedance 100 ± 20 ohms DC Loop Resistance 52 ohms per 1,000ft (18 ohms per 100m) Differential Capacitance 19 pF/ft max (62 pF/m max)
Power	Adaptive Voltage Arrange No external power required
Connector	Video Input Male BNC connector Video Output Screw terminal
Protection	Surge Protection Built-in Transient Voltage Suppressor(TVS) Antistatic Yes Dimensions(L*W*H) 42*18*12mm (BNC connector & cable excluded)
Mechanical	Housing ABS engineering plastic Body Color Black Net Weight 40g
Environmental	Operating Temperature -25° ~ 75° C Relative Humidity 0~95% (non-con) Storage Temperature -40° ~ 150° C